



Temporary Protected Lighting (TPLX)

BENEFITS

- Super compact 200mm lens, lightweight and easily transportable
- Robust long life LED light source
- Colour temperature 6500k
- Daisy chain up to 225m
- Fully enclosed high impact polycarbonate
- Rough Service specification

Unlike standard chain lights that only shine downward, the TPLX radiates light both downward and upward, illuminating not just the ground but also elevated work areas like scaffolding and ladders. This unique feature enhances safety, reducing the risk of accidents in high-risk areas

SPECIFICATIONS

LAMP	24W LED per fitting
LUMENS	2700 lumens (27,000 Total)
LAMP IP RATING	IP68
CONNECTION	10A or 15A flat pin, 16A IEC
VOLTAGE	220V-240V AC (double insulated)
CABLE	2.5mm ² - 3c Flat Flex
LENS	Polycarbonate
LENGTH	25m Standard - 10 Lamps

FEATURES

- Brightest chain light on the market
- Designed and tested to AS/NZS 60598.2.20
- Meet the requirements of AS/NZS 3012 and AS/NZS 3002
- For use within building, construction, shows, events and markets
- Provide reliable site safety and security
- Serviceable by an authorized representative

Part Number	Length	Plug	Lamps	Watts	Voltage	Wire
LG15TPLX2510A	25m	10A	10x LED	240	220-240V AC	2.5mm ²
LG15TPLX2516A	25m	16A	10x LED	240	220-240V AC	2.5mm ²
LG15TPLX12.510A	12.5m	10A	5x LED	120	220-240V AC	2.5mm ²
LG15TPLX12.516A	12.5m	16A	5x LED	120	220-240V AC	2.5mm ²

